

Model JET514 shown

4 times faster than conventional ovens.

Heavy Volume | Combination Cooking This category of combination oven is ideal for...

Application:

- Wine bars
- Country club, - Bakery/cafés
- Pubs - Kiosks
- Convenience stores
- Supermarkets

Through put potential:

- 6" Inch toasted sub sandwiches, 50 per hour
- 1 portion of 4 frozen crispy chicken wings, 25 portions (84 wings) per hour
- 1 frozen pre-baked fruit filled pastry, 20 per hour
- 12" frozen pizza, 10 per hour
- 1 frozen, pre-baked fruit filled pastry, 20 per hour

Location of oven(s):

- Kitchen shelf
- Kitchen countertop, single or stacked
- Equipment stand, single or stacked

All ACP, Inc. commercial ovens are backed by our Culinary Center. Call us with any question regarding food preparation, menu development and cooking times. 866-426-2621.



High Speed Combination Oven Menumaster® Commercial Jetwave™ Model JET514

Power Output

- Convection:
 - 2700 W
 - 65°-250°C (150°-475°F) temperature range
 - Convected air for enhanced toasting and browning
- Microwave:
 - 1400 W
 - Heats quickly, reduces cooking time

Project #:

Cuts Costs

- Uses less energy than a conventional oven.
- Eliminates need for pre-cooking and holding.
- Uses quarter size metal trays, pans and screens.

Simplifies Cooking

- Touch pad operation for consistent results.
- Controls are intuitive and simple to use.
- Stores up to 100 menu items.
- Four stage cooking option.
- USB Port compatible with standard flash drives, updates programming in seconds.
- 34 liter (1.2 cubic ft.) oven capacity.
- Door opens 90°+ for full access to the oven cavity.
- Single rack position for optimal and consistent cooking results.

Easy to Use and Maintain

- Braille touch pads are ADA compliant.
- Stainless steel door and interior.
- Removable, cleanable air filter and clean filter reminder protect oven components.
- Backed by the ACP, Inc. 24/7 ComServ Support Center 866-426-2621.



19 ¼" (489) 0 0 \bigcirc 18-1/8" (460) \bigcirc 41/4" (108)3" (76) 21 1/5" (546) (1016) Installation clearance: 7" for top of oven Drawings available from 2" for all other sides KCL CADlog - techs@kclcad.com

Model JET514 UPC Code 728028244731 2700W 1400W Convection Microwave Configuration Countertop Touch Programmable Control Pads Braille Total Programmable Settings Power Levels 11 Max. Cooking Time 20:00 Stackable Yes Time Entry Option Yes Microwave Distribution Rotating antennas, top Magnetrons 2 Display LED-backlit LCD Stage Cooking Yes, 4 Door Opening Grab & Go USB Port Yes Temperature Range 70° - 250°C (150° - 475°F) Air Filter Yes, removable, with clean filter reminder Rack 1 rack position, removable Exterior Dimensions H 460 (18 ½") W 489 (19 ½") D** 676 (26 ½") Door Depth 994 (39 ½"), 90°+ door open Usable Cavity Space 34 liter (1.2 cubic ft.) Exterior Finish Powder coat painted Interior Finish Stainless steel Power Consumption 2900 W, 13 A Power Output* 1400 W* Microwave Power Source Plug Configuration / Cord Frequency 2450 MHz Product Weight 49 kg. (107 lbs.) Ship weight (approx.)					
Cooking Power* Configuration Control System Programmable Control Pads Braille Total Programmable Settings Power Levels Max. Cooking Time Stackable Time Entry Option Microwave Distribution Magnetrons Display Stage Cooking Door Opening USB Port Temperature Range Air Filter Rack Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) 10 Pres Touch Touch Touch Touch Touch Tinuch Titouch Touch Tinuch Titouch Titouch Titouch Titouch Titouch Touch Titouch T	Specifications				
Cooking Power* Configuration Control System Programmable Control Pads Braille Total Programmable Settings Power Levels Max. Cooking Time Stackable Time Entry Option Microwave Distribution Magnetrons Display Stage Cooking Door Opening USB Port Temperature Range Air Filter Rack Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) Finuch Inconveve (Countertop Touch 10 Microwave Countertop Touch 10 Yes 100 Power Consumption Pyes 11 Aves Rotating antennas, top 2 LED-backlit LCD Yes, 4 Grab & Go Ves, 4 Grab & Go Ves, 4 Food (150° - 475°F) Yes, removable, with clean filter reminder 1 rack position, removable H 460 (18 ½") W 489 (19 ½") D** 676 (26 ½") W 330 (13") D 381 (15") Powder coat painted Stainless steel 290 W, 13 A 1400 W* Microwave 230 V, 50 Hz, 16 A single phase CEE 7/7 Schuko" 1.5 m (5 ft.) Frequency Product Weight Ship weight (approx.) 51 kg. (112 lbs.)	Model	JET514	UPC Code 7280)28244731	
Control System Programmable Control Pads Braille Total Programmable Settings Power Levels Max. Cooking Time Stackable Time Entry Option Microwave Distribution Magnetrons Display Stage Cooking Door Opening USB Port Temperature Range Air Filter Rack 1 rack position, removable Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) I 10 Yes 100 Yes 110 100 11 20:00 Yes 100 11 20:00 11 2	Cooking Power*		1		
Programmable Control Pads Braille Total Programmable Settings Power Levels Max. Cooking Time Stackable Time Entry Option Microwave Distribution Magnetrons Display Stage Cooking Door Opening USB Port Temperature Range Air Filter Rack Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) Pyes 11 20:00 Yes 11 20:00 Yes Rotating antennas, top Rotating antennas, top 2 LED-backlit LCD Yes, 4 Grab & Go Yes, 4 Grab & Go Yes Rotating antennas, top 2 Poves Rotating antennas, top 2 Rotating a	Configuration	Countertop			
Braille Total Programmable Settings Power Levels Max. Cooking Time Stackable Time Entry Option Microwave Distribution Magnetrons Display Stage Cooking Door Opening USB Port Temperature Range Air Filter Rack Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Powder Consumption Usable Cavity Space Exterior Finish Power Consumption Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) 11 20:00 12 20:00 12 20:00 13 20:00 20:	Control System	Touch			
Total Programmable Settings Power Levels Max. Cooking Time Stackable Time Entry Option Microwave Distribution Magnetrons Display LED-backlit LCD Stage Cooking Door Opening USB Port Temperature Range Air Filter Rack 1 rack position, removable Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Interior Finish Power Consumption Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) 100 11 11 20:00 11 11 20:00 11 11 20:00 11 11 20:00 11 11 20:00 11 11 10 10 11 11 10 11 11 11 11 11 1	Programmable Control Pads	10			
Power Levels Max. Cooking Time Stackable Time Entry Option Microwave Distribution Magnetrons Display LED-backlit LCD Stage Cooking Door Opening USB Port Temperature Range Air Filter Rack I rack position, removable Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Interior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) Possible Cavity Space Plug Configuration / Cord Frequency Product Weight Stainless Steel 20:00 Yes LED-backlit LCD Yes, 4 Go Cavity Cloop Ary Se Color - 475°F) Yes, removable, with clean filter reminder 1 rack position, removable Exterior, removable H 460 (18 ½") W 489 (19 ¼") D** 676 (26 ½") W 330 (13") D 381 (15") Dowler Confound By 489 (107 lbs.) Solve A single phase CEE 7/7 "Schuko" 1.5 m (5 ft.) Towler Consumption Product Weight Ship weight (approx.) Solve A single phase CEE 7/7 "Schuko" 1.5 m (5 ft.) Frequency Product Weight Ship weight (approx.)	Braille	Yes			
Max. Cooking Time Stackable Time Entry Option Microwave Distribution Magnetrons Display LED-backlit LCD Stage Cooking Door Opening USB Port Temperature Range Air Filter Rack I rack position, removable Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) Possible Adating antennas, top Rotating antennas, top Rotating antennas, top Rotating antennas, top Yes LED-backlit LCD Yes, 4 Grab & Go Yes 1.5 m (5 ft.) Yes A 4 5° F) Yes A 50° - 250°C (150° - 475°F) Yes Temperature Range A 70° - 250°C (150° - 475°F) Yes Toro - 250°C (150° - 475°F) Yes Toro - 250°C (150° - 475°F) Yes Toro - 250°C (150° - 475°F) W 489 (19 ¼") D** 676 (26 %") D** 676 (26 %") D** 676 (Total Programmable Settings	100			
Stackable Time Entry Option Microwave Distribution Magnetrons Display Display Door Opening USB Port Temperature Range Air Filter Rack 1 rack position, removable Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) Possible Cavity Display Possible Cappox Possible	Power Levels	11			
Time Entry Option Microwave Distribution Magnetrons Display LED-backlit LCD Stage Cooking Door Opening USB Port Temperature Range Air Filter Rack I rack position, removable Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Stainless steel Possible Cavity Space Possible Cavity Cord Product Weight Possible Cavity Space Possible Cavity Cord Possib	Max. Cooking Time	20:00			
Microwave Distribution Magnetrons Display LED-backlit LCD Stage Cooking Yes, 4 Door Opening USB Port Temperature Range Air Filter Rack Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Interior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Mega (10 / 2) Possible A single phase CEE 7/7 "Schuko" Frequency Product Weight Stainless steel Possible Cavity Space 24 So MHz Product Weight A single phase CEE 7/7 "Schuko" Stain (12 lbs.)	Stackable	Yes			
Display Display LED-backlit LCD Stage Cooking Door Opening Grab & Go USB Port Temperature Range Air Filter Rack Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) Power Conking Display Yes, removable, with clean filter reminder Yes, removable, with clean filter reminder Rack 1 rack position, removable W 489 (19 ¼") D** 676 (26 %") W 489 (19 ¼") D** 676 (26 %") W 330 (13") D 381 (15") Dower Goavity Dimensions H 267 (10 ½") W 330 (13") D 381 (15") Dower Goavity Space Stainless steel Powder coat painted Stainless steel Power Consumption 1400 W* Microwave Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) 15 kg. (112 lbs.)	Time Entry Option	Yes			
Display Stage Cooking Pes, 4 Door Opening Grab & Go USB Port Temperature Range Air Filter Rack Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Interior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Share Door Opening Stage Cooking Yes, 4 Grab & Go Yes Yes, removable Ves, removable, with clean filter reminder I rack position, removable W 489 (19 ¼") D** 676 (26 ½") W 330 (13") D 381 (15") Dow* 489 (19 ¼") D** 676 (26 ½") W 330 (13") D 381 (15") Dow* 676 (26 ½") W 330 (13") D 381 (15") Dow* 676 (26 ½") W 489 (19 ¼") D** 676 (26 ½") D*	Microwave Distribution	Rotating antennas, top			
Stage Cooking Door Opening USB Port Temperature Range Air Filter Rack Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) Power Source Pus Grab & Go Grab & Go Grab & Go Grab & Go Yes Grab A Free G	Magnetrons	2			
Door Opening USB Port Temperature Range Air Filter Rack Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Stain Ess Seel Possible Cavity Captor (2450 MHz Pord Captor (2450 MHz Power Garban (2450 MHz Power Gutput (2450 MHz Pord Captor (2450 MHz Power Gutput (2550 MHz Power Gutput (2550 MHz Power Gutput (2450 MHz Power Gu	Display	LED-backlit LCD			
USB Port Temperature Range Air Filter Rack 1 rack position, removable Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Power Gange (100 Mars) Power Gange (100 Mars) Power Gange (100 Mars) Power Source Plug Configuration / Cord Temperature Range 70° - 250°C (150° - 475°F) Pyes, removable, with clean filter reminder 1 rack position, removable Pow 489 (19 ¼") Pow 489 (19 ¼") Pow 489 (19 ¼") Pow 489 (19 ¼") Pow 489 (107 lbs.) Power A475°F) W 489 (107 lbs.) Power A475°F) W 489 (107 lbs.) Power A475°F) W 489 (150° - 475°F) W 489 (150° - 475°F) W 489 (19 ¼") Power A475°F) W 489 (19 ¼") D ** 676 (26 ½") D	Stage Cooking	Yes, 4			
Temperature Range Air Filter Rack 1 rack position, removable Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Pixes Power Marcol Power (10 Mg) Power Marcol Power (10 Mg) Power Marcol Power (150° - 475°F) Yes, removable, with clean filter reminder 1 rack position, removable Power 489 (19 ¼") Power 489 (19 ¼") Power 489 (19 ¼") Power 490 (18 ½") Power 490 (18 ½") W 489 (19 ¼") W 489 (19 ¼") D** 676 (26 ½") D*	Door Opening	Grab & Go			
Air Filter Rack 1 rack position, removable Exterior Dimensions Cavity Dimensions Door Depth Usable Cavity Space Exterior Finish Interior Finish Power Consumption Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) Pare Ado (18 1/8") W 489 (19 1/4") W 489 (19 1/4") W 330 (13") D 381 (15") D 381 (15") D 381 (15") Powe Ador open 34 liter (1.2 cubic ft.) Powder coat painted Stainless steel Powder Consumption 2900 W, 13 A 1400 W* Microwave 230 V, 50 Hz, 16 A single phase CEE 7/7 "Schuko" 1.5 m (5 ft.) 151 kg. (112 lbs.)	USB Port	Yes			
Rack Exterior Dimensions H 460 (18 1/8") W 489 (19 1/4") D** 676 (26 1/8") Cavity Dimensions H 267 (10 1/2") W 330 (13") D 381 (15") Door Depth Usable Cavity Space Exterior Finish Powder coat painted Interior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) 1 rack position, removable D 489 (19 1/4") D 2* 676 (26 1/8") D 381 (15") D 381	Temperature Range	70° - 250°C (150° - 475°F)			
Exterior Dimensions Cavity Dimensions H 460 (18 1/2") W 489 (19 1/4") D** 676 (26 5/8") H 267 (10 1/2") W 330 (13") D 381 (15") D 381 (15") 994 (39 1/8"), 90°+ door open 34 liter (1.2 cubic ft.) Exterior Finish Powder coat painted Interior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Stainless steel 2900 W, 13 A 1400 W* Microwave 230 V, 50 Hz, 16 A single phase CEE 7/7 "Schuko" 1.5 m (5 ft.) Frequency 49 kg. (107 lbs.) Ship weight (approx.) 51 kg. (112 lbs.)	Air Filter	Yes, removable, with clean filter reminder			
Cavity Dimensions Door Depth 994 (39 1/8"), 90°+ door open 34 liter (1.2 cubic ft.) Exterior Finish Interior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Stainless steel 2900 W, 13 A 1400 W* Microwave 230 V, 50 Hz, 16 A single phase CEE 7/7 "Schuko" 1.5 m (5 ft.) •• 151 kg. (112 lbs.)	Rack	1 rack position, removable			
Door Depth Usable Cavity Space Exterior Finish Powder coat painted Interior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Stainless steel 2900 W, 13 A 1400 W* Microwave 230 V, 50 Hz, 16 A single phase CEE 7/7 "Schuko" 1.5 m (5 ft.)	Exterior Dimensions	H 460 (18 1/8")	W 489 (19 ¼")	D** 676 (26 5/8")	
Usable Cavity Space Exterior Finish Interior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Stainless steel 2900 W, 13 A 1400 W* Microwave 230 V, 50 Hz, 16 A single phase CEE 7/7 "Schuko" 1.5 m (5 ft.) •• 15 kg. (112 lbs.)	Cavity Dimensions	H 267 (10 ½")	W 330 (13")	D 381 (15")	
Exterior Finish Interior Finish Powder coat painted Stainless steel Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) Powder coat painted Stainless steel Powder Coat painted Stai	Door Depth	994 (39 1/8"), 90°+ door open			
Interior Finish Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Stainless steel 2900 W, 13 A 1400 W* Microwave 230 V, 50 Hz, 16 A single phase CEE 7/7 "Schuko" 2450 MHz 49 kg. (107 lbs.) 51 kg. (112 lbs.)	Usable Cavity Space	34 liter (1.2 cub	34 liter (1.2 cubic ft.)		
Power Consumption Power Output* Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) 2900 W, 13 A 1400 W* Microwave 230 V, 50 Hz, 16 A single phase CEE 7/7 "Schuko" 2450 MHz 49 kg. (107 lbs.) 51 kg. (112 lbs.)	Exterior Finish	Powder coat painted			
Power Output* 1400 W* Microwave 230 V, 50 Hz, 16 A single phase CEE 7/7 "Schuko" 1.5 m (5 ft.) Frequency 2450 MHz Product Weight 49 kg. (107 lbs.) Ship weight (approx.) 51 kg. (112 lbs.)	Interior Finish	Stainless steel			
Power Source Plug Configuration / Cord Frequency Product Weight Ship weight (approx.) 230 V, 50 Hz, 16 A single phase CEE 7/7 "Schuko" 2450 MHz 49 kg. (107 lbs.) 51 kg. (112 lbs.)	Power Consumption	2900 W, 13 A			
Plug Configuration / Cord CEE 7/7 "Schuko" 1.5 m (5 ft.) Frequency Product Weight 49 kg. (107 lbs.) Ship weight (approx.) 51 kg. (112 lbs.)	Power Output*	1400 W* Microwave			
Plug Configuration / Cord "Schuko" 1.5 m (5 ft.) ••• Frequency 2450 MHz Product Weight 49 kg. (107 lbs.) 51 kg. (112 lbs.)	Power Source				
Product Weight 49 kg. (107 lbs.) Ship weight (approx.) 51 kg. (112 lbs.)	Plug Configuration / Cord		1.5 m (5 ft.)	•••	
Ship weight (approx.) 51 kg. (112 lbs.)	Frequency	2450 MHz			
	Product Weight	49 kg. (107 lbs.)			
CI:	Ship weight (approx.)	51 kg. (112 lbs.)			
Shipping Carton Size H 546 (21 ½") W 546 (21 ½") D 756 (29 ¾")	Shipping Carton Size	H 546 (21 ½")	W 546 (21 ½")	D 756 (29 ¾")	

Specifications

Oven shall combine two cooking modes: convection and microwave for high speed cooking. Control panel shall be programmable with the ability to program up to 100 menu items, single or double digit entry. Programs shall be automatically updated using a USB Port that is compatible with standard USB flash drives. There shall be 11 power levels and 4 cooking stages. Microwave output shall be 1400 watts and distributed from the top of the cavity. The 2700 watt convection oven shall provide a temperature range from 70° - 250° C (150° - 475° F) in 5° increments. The convection fan located in the back of the cavity shall distribute the heat throughout the cavity to further enhance browning. Maximum microwave cooking time shall be 20 minutes. Oven shall have a powder coat exterior. 34 liter (1.2 cubic ft.) oven cavity shall be stainless steel construction with stainless oven door. Interior shall have 1 rack position. Air filter shall be easily accessible and removable from the front of the oven and have a "clean filter" reminder feature. Oven shall be stackable. Microwave oven shall comply with standards set by the U.S Department of Health and Human Services and ETL listed for safety and sanitation.

Optional Accessories

- Pizza stone
- Drip tray
- Oven paddle

Warrantv

Warranty Certificate for this product can be found on the ACP, Inc. website at:

www.acpsolutions.com/warranty

Service

All products are backed by the ACP, Inc. 24/7 ComServ Support Center.





Measurements in () are in inches * IEC 60705 Tested ** Includes handle

225 49th Ave. Dr. SW Cedar Rapids, IA 52404 U.S.A.

Part No. 20154105 Updated 12/17/14 **Original Instructions**



©2014 ACP, Inc. Cedar Rapids, Iowa 52404